



10 CONNECTOR A		
TWINTUS / 18-Pole / female / straight		
Crimp Contact:	7.010.980.802 (18x)	
M16 Inserts, 18-Pole:	7.003.988.102	
M16 Connector:	7.810.400.000	
Contact Resistance	mΩ	<3
Contact Material	Nickel- and Gold-Plated	
Contact Carrier Material	PA 6, PBT	
Connector Body Material	Copper-Zinc Alloy, Nickel-Plated	
Coupling (Nut / Screw)	Copper-Zinc Alloy, Nickel-Plated	
O-Ring Material	NBR	
Protection Class	IP67 (locked Condition)	
Function	Pin No.	Color
Output 1	1	WH/YE
Output 2	2	YE/BN
Output 3	3	WH/GY
Analog Input	4	WH/BU
+UB extern	5	WH/PK
GND (W001)	6	RD
RS485 Tx+	7	GY
RS485 Tx-	8	PK
RS485 Rx-	9	YE
RS485 Rx+	10	GN
Input 1	11	BK
Input 2	12	VT
Input 3	13	GY/PK
Input 4	14	RD/BU
Input 5	15	WH/GN
Input 6	16	BN/GN
CAN -	17	WH
CAN +	18	BN

20 CABLE SPECIFICATION		
LAPP UNITRONIC LiYCY (TP)		
Cable Length	mm	9955
Cable Diameter	mm	8.9
Cable Material	PVC	
Cable Color	Grey	
Conductor Insulation	PVC	
Conductor / Cross - Section	mm ²	12x2x0.14
UL Type	No	
Shielded	Yes	
Bending Radius (flexible)	Min. 15 x Ø	
Bending Radius (stationary)	Min. 6 x Ø	

30 Cable End Sleeve		
Cable End Sleeve	(18x)	8 mm, Grey

ISO 8015		ISO 1302		ISO 2768 cK		ISO 13715	
Drawn	24.04.2018	Name		Schneid_A			
Checked	30.01.2019	Name		Reith_S			
Approved	30.01.2019	Name		Schneid_A			
02	revise drawing	Schneid_A	30.01.2019				
REV	Rev. Text	Name	Rel. Date				

Weight: 1.2 kg		ZK-TW-18-10M		
14200108				
State: Released	Rev: 02	P		

GENERAL SPECIFICATION		
Rated Current	A	3
Rated Voltage	VAC/DC	24
Insulation resistance	MΩ	>10 ³
Ambient temperature	-5°C...+70°C	