



| 10 CONNECTOR A | | |
|--------------------------|-------------|--------|
| 6-Pole Micro Connector | | |
| Contact Resistance | mΩ | n. a. |
| Contact Material | | n. a. |
| Contact Carrier Material | | n. a. |
| Connector Body Material | | n. a. |
| Protection Class | | n. a. |
| Pin No. | Function | Colour |
| 1 | GND | BK |
| 2 | A | BU |
| 3 | A\ | OG |
| 4 | +5VDC Power | RD |
| 5 | B | YE |
| 6 | B\ | GY |

| 20 CABLE SPECIFICATION | | |
|-----------------------------|----|-------|
| 6x Conductor round cable | | |
| Cable Length | mm | 610 |
| Cable Diameter | mm | n. a. |
| Cable Material | | n. a. |
| Cable Color | | - |
| Conductor Insulation | | n. a. |
| Conductor / Cross - Section | | AWG26 |
| UL Type | | n. a. |
| Shielded | | No |
| Bending Radius (flexible) | | n. a. |
| Bending Radius (stationary) | | n. a. |

| GENERAL SPECIFICATION | | |
|-----------------------|--------|-------|
| Rated Current | A | n. a. |
| Rated Voltage | VAC/DC | n. a. |
| Insulation resistance | MΩ | n. a. |
| Ambient temperature | | n. a. |

| ISO 8015 | ISO 1302 | ISO 2768-1 cK | ISO 13715 | Weight: 0.09 kg |
|----------|-----------|---------------|-----------|-------------------------|
| | | | Date | Name |
| | | | Drawn | 07.08.2019 Schneid_A |
| | | | Checked | 08.08.2019 Rehse_P |
| | | | Approved | 08.08.2019 Rehse_P |
| REV | Rev. Text | Name | Rel. Date | |
| | | | | |

| | |
|---------------------|------|
| ZK-NTO4L-610 | |
| 14200259 | - |
| State: Released | A4-Q |
| Rev: - | P |